

FACT SHEET TEXTILE "OSLO SUEDE"

Description

Fabric for upholstery, curtains, and cushions.

Components

- **Composition Top:** 100% Polyester
- **Composition Base:** 45% Polyester + 35% PU + 20% Cotton
- **Weight:** 700 gr/lm (+-5%)
- **Width:** 140 cm (+-3%)

Physical Properties

| Properties | Result | Standards |
|------------------------------------|-------------|------------------|
| Pilling Resistance | 4 | EN ISO 12945-2 |
| Abrasion Resistance – end of test | 35.000 | EN ISO 12947-1,2 |
| Tensile Strength | Warp 1276 N | EN ISO 13934-1 |
| | Weft 998 N | EN ISO 13934-1 |
| Seam Strength | Warp 2,3 mm | EN ISO 13936-2 |
| | Weft 2,0 mm | EN ISO 13936-2 |
| Tear Resistance | Warp 72,9 N | EN ISO 13937-3 |
| | Weft 49,9 N | EN ISO 13937-3 |
| Color Fastness to Rubbing | Dry 5 | EN ISO 105-X12 |
| | Wet 4 | EN ISO 105-X12 |
| Color Fastness to Artificial Light | 4 | EN ISO 105-B02 |
| Fire Resistance | PASS | EN ISO 1021-1 |
| Fire Resistance | PASS | BS 5852-1 |

Features

- **Hydrolysis Resistance (10 years)**
- **Easy Care**
- **Environmentally Friendly**

Presentation

- **Piece:** 30/35 meters

Conservation



WASH



BLEACH



DRY



IRON



DRYCLEAN

